

External works spec and quote:

- Break out existing damaged concrete marked and measured by client, excavate down 350mm and cart away.
- Any soft spots to be excavated and filled with compacted MOT Type1.
- Level and compact Mot type 1 to a depth of 150mm below new concrete slabs.
- Tie mesh A393 10mm mesh top and bottom on 40mm spaces with 100mm steel chairs between.
- 12mm starter bars to have minimum 600 splice.
- Concrete surface to have a tamped finish with expansion joints of 25mm compressive board on any 5m or above stretch of slab with span flex or similar and jointed with flexible sealant.
- Concrete curing agent to be used on all slabs.
- All C&C waist to be removed and site area cleared and cleaned

Cost: 73,600 +VAT

- Commencement of works £30,520
- Reinforcement tied ready ££30,520
- Completion of works £30,520

Qualifications:

- Ground being assumed as clean, inert and free from obstructions.
- No provision for working around live services has been made.
- Works are priced in boundary of project only.
- Quote is valid for 60 days.
- Day work rates to be agreed pre start if needed.
- Any retention due 30 days after completion.
- Fully qualified and certified SMSTS manager and engineer on site at all times.
- 10-year guaranty will be issued on final payment.
- All works fully insured

Regards

Joseph Cousin Snr Engineer 07760396423